



Type K PTFE Insulated Twin Twisted Pair Thermocouple Cable / Wire (IEC)




10m



TYPE-K

50M



TYPE-K

Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

Type K PTFE Insulated Twin Twisted Pair Thermocouple Cable / Wire (IEC)

PTFE insulated twin twisted pair. PTFE has a good mechanical strength and flexibility, resistant to oils, acids and other adverse fluids.

Specifications
Specifications

| | |
|---|---|
| General Description | Resistant to oils, acids adverse agents and fluids. Good mechanical strength and flexibility. |
| Cable Length | 10m, 25m, 50m, 100m |
| Cable Type | Twin twisted pair for extending or making simple thermocouples |
| Core / Strands | 1/0.2mm / 1/0.508mm, 1/0.315mm, 7/0.2mm |
| Conductor Cross Section 1/0.2 (mm²) | 0.032 |
| Conductor Cross Section 1/0.315 (mm²) | 0.078 |
| Conductor Cross Section 1/0.508 (mm²) | 0.203 |
| Conductor Cross Section 7/0.2 (mm²) | 0.219 |
| + Colour | Green |
| - Colour | White |
| Drain Wire | No |

| | |
|--|---|
| Insulation Material | PTFE insulated |
| Loop Resistance 1/0.2 (Ohms per combined metre) | 31.8 |
| Loop Resistance 1/0.315 (Ohms per combined metre) | 12.8 |
| Loop Resistance 1/0.508 (Ohms per combined metre) | 4.9 |
| Loop Resistance 7/0.2 (Ohms per combined metre) | 4.5 |
| Max. Temperature | +260°C |
| Min. Temperature | -75°C |
| + Conductor | Nickel Chromium |
| - Conductor | Nickel Aluminium |
| Screen | No |
| Standards Met | Colour code (cores & jacket) to IEC-584-3 |
| Thermocouple Type | K |
| Tolerance | Class 1 |