

## DishTemp Blue Dishwasher Thermometer



Labfacility are the UK's leading manufacturer of Temperature Sensors, Thermocouple Connectors and associated Temperature Instrumentation and stockings of Thermocouple Cables. The Company has been trading since 1971 and is ISO9001 accredited.

DishTemp® Blue Bluetooth® LE dishwasher thermometer

- Simulates maximum plate surface temperatures
- Waterproof to IP66
- HACCP compatible
- FREE 1-point traceable certificate of calibration at 71°C

Now available as a Bluetooth® model the DishTemp® Blue Dishwasher Thermometer transmits temperature data to your iOS, Android or Bluetooth wireless device via a secure connection of up to 6 metres.

Specifically designed to save time, paper and eliminate human error when recording temperature cycles. The DishTemp Blue simulates a plate as it's cleaned and sanitised in a commercial dishwasher, accurately recording the maximum surface temperature at the touch of a single button, eliminating the need for costly and inaccurate test strips and stem thermometers that do not stay in place or record the surface temperature of a plate.

Built to survive daily use in professional kitchens, the DishTemp Blue dishwasher thermometer indicates temperature over the range of 0 to 90 °C with a resolution of 0.1 °C/°F and an accuracy of ±0.5 °C.

Incorporating a durable water-tight seal, the DishTemp Blue is supplied complete with a FREE 1-point traceable certificate of calibration @ 71°C

Specifications

## Specifications

<b>Product Code</b>	XE-3935-001
<b>Model</b>	DishTemp Blue Dishwasher Thermometer
<b>General Description</b>	Flexible sheath can be bent/formed to suit many applications and processes
<b>Type</b>	Celsius/Fahrenheit
<b>Communications Protocol</b>	Bluetooth LE
<b>Accuracy</b>	+/-0.5°C
<b>Resolution</b>	0.1 °C/°F
<b>Battery</b>	3 volt CR2032 lithium coin cell - 40 hours life
<b>Connector Type</b>	Plug
<b>Connector Size</b>	Miniature (moulded-on)
<b>Dimensions</b>	14 x O127mm
<b>Element/hot junction</b>	Single element, grounded junction offering fast response
<b>Display Type</b>	Custom LCD
<b>Max. Temperature</b>	+260°C (Moulded-on plug +110°C)
<b>Min. Temperature</b>	-50°C
<b>Input / Ranges</b>	6 metres
<b>Temperature Range</b>	0 to 90°C

<b>Probe Diameter</b>	3.3mm
<b>Probe Length</b>	80mm
<b>Probe Material</b>	Needle point tip, 316 stainless steel
<b>Weight</b>	120 grams
<b>Sensor Type</b>	Mineral insulated
<b>Calibration</b>	FREE 1-point traceable calibration certificate at 71°C
<b>Standards Met</b>	IP66
<b>Thermocouple Type</b>	K
<b>Termination Type</b>	Miniature moulded flat pin plug, colour coded 'green' in accordance IEC specification
<b>Construction</b>	ABS plastic
<b>Guarantee</b>	1 Year